

# LOR LIGHTING TECHNOLOGY CO.,LTD

Tel:+86-760-22781396 Fax:+86-760-22833880

www.lorlighting.com

# LOR

## SPECIFICATION

|                         |                       |                  |     |                   |
|-------------------------|-----------------------|------------------|-----|-------------------|
| <b>Item No:</b>         | <b>LRTLJ047-A1</b>    |                  |     |                   |
| Product Category        | Down light            |                  |     |                   |
| Installation            | Recessed              |                  |     |                   |
| IP Grade                | IP 20                 |                  |     |                   |
| Beam Angle              | 15/28/40              |                  |     |                   |
| Power Consumption       | 25W                   |                  |     |                   |
| Dimension               | 130*150mm             |                  |     |                   |
| Cut out                 | Φ140mm                |                  |     |                   |
| Ambient Temperature     | -20℃~45℃              |                  |     |                   |
| Finishing Color         | WH/BK                 |                  |     |                   |
| Optical Parameters      |                       |                  |     |                   |
| LED Source              | CREE                  |                  |     |                   |
| Lamp Life               | 35000-50000H          |                  |     |                   |
| <b>Center intensity</b> |                       |                  |     |                   |
| Clour Temperature       | Initial Lumen         | Lumen Efficiency | CRI | Color Differenc e |
| 3000/4000               | 2375lm                | 95lm/w           | >80 | ≤ 3 steps         |
| Power Model             | Philips               |                  |     |                   |
| Dimmable                | Dimmable/Non-dimmable |                  |     |                   |
| Input Voltage           | 220-240V              |                  |     |                   |
| Input Current Frequency | 50HZ / 60HZ           |                  |     |                   |
| Output Voltage          | 37V                   |                  |     |                   |
| Output Current          | 600MA                 |                  |     |                   |
| Power factor            | ≥0.9                  |                  |     |                   |



## Packaging

|               | L (cm) | W (cm) | H (cm) | N . W. (Kg) | Pack Qty (pcs) |
|---------------|--------|--------|--------|-------------|----------------|
| Inner Package |        |        |        |             |                |
| Outer Package |        |        |        |             |                |

Others:

Safety

Warranty three year